



# CamWave 5 GHz (5000 MHz) Frequency Allocation Chart

10182013

Chart 1 Center Frequency (20MHz Increments)

5000-6000 MHz	5020	5040	5060	5080	5100	5120	5140	5160	5180	5200	5220	5240	5260	5280	5300	5320	5340	5360	5380	5400	5420	5440	5460	5480	5500	5520	5540	5560	5580	5600	5620	5640	5660	5680	5700	5720	5740	5760	5780	5800	5820	5840	5860	5880	5900	5920	5940	5960	5980	
CW-5HD									5180	5200	5220																											5745	5765	5785	5805	5825								
20MHz Channel									3/A1	A2	4/A3																										1/A4	A5	A6	A7	2/A8									
CW-7									5190	5230	5270	5310														5510	5550											5755	5795											
40 MHz Channel									1	2	DFS 1	DFS 2														DFS 3	DFS 4										3	4												
CW-1													5270	5310												5510	5550																							
40 MHz Channel													DFS 1	DFS 2												DFS 3	DFS 4																							
U-NII Band									U-NII-1 5150-5250 MHz				U-NII-2 DFS 5250-5350 MHz				U-NII-2e DFS 5470-5725 MHz										U-NII-3 5725-5825 MHz																							

table 1

Model	Channel	Frequency MHz	Bandwidth	High Power	Low Power
<b>CW-5HD</b>	1	5745	20 MHz	50 mW	5 mW
	2	5825	20 MHz	50 mW	5 mW
	3	5180	20 MHz	14.5 mW	5 mW
	4	5220	20 MHz	14.5 mW	5 mW
	Auto 1	5180	20 MHz	14.5 mW	5 mW
	Auto 2	5200	20 MHz	14.5 mW	5 mW
	Auto 3	5220	20 MHz	14.5 mW	5 mW
	Auto 4	5745	20 MHz	50 mW	5 mW
	Auto 5	5765	20 MHz	50 mW	5 mW
	Auto 6	5785	20 MHz	50 mW	5 mW
	Auto 7	5805	20 MHz	50 mW	5 mW
Auto 8	5825	20 MHz	50 mW	5 mW	

table 2

Model	Channel	Frequency MHz	Bandwidth	High Power	Low Power
<b>CW-7</b>	1	5190	40 MHz	50 mW	5 mW
	2	5230	40 MHz	50 mW	5 mW
	3	5755	40 MHz	80 mW	5 mW
	4	5795	40 MHz	80 mW	5 mW
	DFS 1	5270	40 MHz	80 mW	5 mW
	DFS 2	5310	40 MHz	80 mW	5 mW
	DFS 3	5510	40 MHz	80 mW	5 mW
	DFS 4	5550	40 MHz	80 mW	5 mW
	DFS 5	5670	40 MHz	80 mW	5 mW

table 3

Model	Channel	Frequency MHz	Bandwidth	Transmit Power (MAX)
<b>CW-1</b>	DFS 1	5270	40 MHz	32 mW
	DFS 2	5310	40 MHz	32 mW
	DFS 3	5510	40 MHz	32 mW
	DFS 4	5550	40 MHz	32 mW
	DFS 5	5670	40 MHz	32 mW

table 4

U-NII Section	Frequency Range	Max Allowed Power Output
U-NII-1	5150-5250 MHz	50 mW
U-NII-2	5250-5350 MHz	250 mW
U-NII-2e	5470-5725 MHz	250 mW
U-NII-3	5725-5825 MHz	1 W

IDX System Technology, Inc.  
 19001 Harbortgate Way, Suite 105  
 Torrance, CA 90501  
 U.S.A.  
 Telephone: (310) 328-2850  
 Fax: (310) 328-8202

For further information, email us: [idx.usa@idx.tv](mailto:idx.usa@idx.tv) or visit our website [www.idxtek.com](http://www.idxtek.com)  
 IDX reserves the right to change the specifications contained herein without notice.

